STATE-BASED MODE SWITCHING WITH APPLICATIONS TO MIXED-CRITICALITY SYSTEMS

Pontus Ekberg, Martin Stigge, Nan Guan & Wang Yi

Uppsala University, Sweden

WMC 2013

MIXED CRITICALITY AS MODE SWITCHING

The common sporadic MC mode switch protocol

At a switch between modes (e.g., LO to HI), each task is either

- 1 suspended and has its active jobs discarded or
- **2** *continues as before*, but with new parameters (*C*, *D*, *T*). The new values of *C* and *D* are immediately used for all active jobs.


MIXED CRITICALITY AS MODE SWITCHING


The common sporadic MC mode switch protocol


At a switch between modes (e.g., LO to HI), each task is either


- 1 suspended and has its active jobs discarded or
- **2** *continues as before*, but with new parameters (*C*, *D*, *T*). The new values of *C* and *D* are immediately used for all active jobs.

Purely sporadic both before and after switch!





























REVISITING AN OLD FRIEND

The common sporadic MC mode switch protocol

At a switch between modes (e.g., LO to HI), each task is either


- suspended and has its active jobs discarded or
- **2** *continues as before*, but with new parameters (*C*, *D*, *T*). The new values of *C* and *D* are immediately used for all active jobs.


REVISITING AN OLD FRIEND


The common sporadic MC mode switch protocol


At a switch between modes (e.g., LO to ні), each task is either


- 1 suspended and has its active jobs discarded or
- **2** *continues as before*, but with new parameters (*C*, *D*, *T*). The new values of *C* and *D* are immediately used for all active jobs.
































Example: Sporadish Dual-Criticality Tasks




Standard high-criticality sporadic task.

EXAMPLE: SPORADISH DUAL-CRITICALITY TASKS




Standard low-criticality sporadic task.

EXAMPLE: SPORADISH DUAL-CRITICALITY TASKS




Low-criticality sporadic task that finishes all jobs.

Example: Sporadish Dual-Criticality Tasks




Task that drops active job at switch, then restarts after a grace period.

EXAMPLE: SPORADISH DUAL-CRITICALITY TASKS





One-off job at mode switch, modeling overhead.


Example: Sporadish Dual-Criticality Tasks





Direct extension of non-sporadic task to dual-criticality semantics.


















































- · Combine techniques from
 - 1 EDF analysis of regular DRT tasks (Stigge et al., 2011) and
 - **2** EDF analysis of MC sporadic tasks (*Ekberg & Yi, 2013*).
- Both based on demand bound functions



- · Combine techniques from
 - 1 EDF analysis of regular DRT tasks (Stigge et al., 2011) and
 - EDF analysis of MC sporadic tasks (Ekberg & Yi, 2013).
- Both based on demand bound functions



- Combine techniques from
 - 1 EDF analysis of regular DRT tasks (Stigge et al., 2011) and
 - 2 EDF analysis of MC sporadic tasks (Ekberg & Yi, 2013).
- Both based on demand bound functions



- · Combine techniques from
 - 1 EDF analysis of regular DRT tasks (Stigge et al., 2011) and
 - 2 EDF analysis of MC sporadic tasks (Ekberg & Yi, 2013).
- Both based on demand bound functions!

∀Thank you!



 \exists Questions?